



NIKOLAN 4-series outdoor cables provide excellent performance at a reasonable price, which makes them the best choice for building networks. Rigid polyethylene shell is not afraid of ultraviolet, it is resistant to cold and external influences. The model range includes shielded (F / UTP) and unshielded (U / UTP) cables of categories 5e and 6, intended for external installation, incl. Suspended, with stranded steel cable. Depending on the model, external cables of the 4th series are delivered in "easy-pull box" cartons or on plywood drums.

Unshielded cables (U / UTP) are the most popular and easy to install type of cable, but they do not have protection against electromagnetic interference. When laying in close proximity to the power lines, it is recommended to refer to shielded solutions.

### Ordering Table

P/N	Number of pairs	Category	Type	Application	Color	Length, M	Volume, m3	Weight, kg
NKL 4700B-BK	4	5e	F/UTP	Outdoor, PE	Black	305	0.0370	11.8
NKL 4701B-BK	4	5e	F/UTP	Outdoor, PE	Black	100	0.0094	3.9

## Detailed characteristics

Characteristic	Value
Category	5e
Bandwidth, MHz	100
Type	F/UTP
Number of pairs	4
Material of conductors	Copper
Type of conductors	Solid
Diameter of conductors, AWG	24 AWG (0.50 ± 0.01 mm)
Insulation material	High density polyethylene (HDPE)
Insulation conductor thickness, mm	0.25 ± 0.02
Diameter of conductor insulation, mm	1 ± 0.05
Outer jacket material	Polyethylene (PE)
Application	For Outdoor Installation
Jacket thickness, mm	0.55 ± 0.05
Outer jacket diameter, mm	6.2 ± 0.3
Jacket color	Black
Screen construction (common screen)	Polyester aluminum foil with 100% coverage, paved in constant contact with a monolithic drainage conductor (26 AWG)
Protective film	Polyester
Ripcord	Yes
Mass density (kg) per unit length (km)	42 ± 0.5
Radius of bending during laying	At least 10 cable diameters
Radius of bending during operation	At least 8 cable diameters
Maximum tensile strength	No more than 100 N
Characteristic impedance, ohms	100 ± 15
Nominal velocity of propagation (NVP)	0.69 ± 0.1
Max. Conductor resistance(DC), ohms/km	95
Length, M	305
Compliance	Exceeds the requirements of the standards: ISO / IEC 11801, EN 50173 and ANSI / TIA-568-C.2
Supported applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 10GBASE-T (For Cat.6), ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges	Storage from -60 to +60 ° C. Installation from -10 to +50 ° C. Operation from -60 to +60 ° C
Individual packing	Cardboard box
Package dimensions (LxW or W x H x D), mm	420x420x210
Warranty	3 years