

NKL-F-xxxM3TG-02B-BK

NIKOLAN Fiber-Optic Cable, Multimode 50/125 OM3, Uni Loose Tube, With Corrugated Steel tape & E - glass yarn, Outdoor, PE Jacket, Black



NIKOLAN cables, with corrugated steel tape and E - glass yarn are designed for laying in the cable sewerage, blocks, tunnels, collectors, on bridges and flyovers, in ground of 1 - 3 groups, between buildings and structures. NKL-F-xxxyTG-02B-BK cables are designed for outdoor installation and contain two, four, six, eight, twelve, sixteen and twenty four optical fibers. Optical cables can be made with fibers comply with the following standard: ITU-T G652.D., ISO/IEC 11801 OS2/OM2/OM3/OM4. Optical fibers are laid in the loose tube, which is filled with a hydrophobic gel. E - glass yarn is used as strength member. Loose tube covered steel tape. The outer jacket is made of PE, resistant to ultraviolet radiation.

Ordering Table

P/N	Number of fibers	Fiber type	Jacket	Individual package	
				Volume, m3	Weight, kg
NKL-F-016M3TG-02B-BK16		MM 50/125 OM3	PE	-	-
NKL-F-024M3TG-02B-BK24		MM 50/125 OM3	PE	-	-
NKL-F-006M3TG-02B-BK6		MM 50/125 OM3	PE	-	-
NKL-F-008M3TG-02B-BK8		MM 50/125 OM3	PE	-	-
NKL-F-012M3TG-02B-BK12		MM 50/125 OM3	PE	-	-
NKL-F-002M3TG-02B-BK2		MM 50/125 OM3	PE	-	-
NKL-F-004M3TG-02B-BK4		MM 50/125 OM3	PE	-	-

Detailed characteristics

Characteristic	Value
CPR Class	Fca
Outer jacket material	PE
Application	Outdoor
Mass density (kg) per unit length (km)	31 kg/km / 31 kg/km / 31 kg/km / 31 kg/km / 31 kg/km / 36 kg/km / 36 kg/km
Maximum tensile strength	1000N
Warranty	Component - 5 years. 25 years - as part of a certified NIKOMAX SCS
Packaging	Wooden drum
Temperature ranges	Transportation and storage from -50 to +70 ° C. Laying and installation from -20 to +60 ° C. Operation -40 to +60 ° C
Diameter of cable	6.5 mm / 6.5 mm / 6.5 mm / 6.5 mm / 6.5 mm / 7.0 mm / 7.0 mm
Number of fibers	2 / 4 / 6 / 8 / 12 / 16 / 24
Type of optical fiber	Multimode fiber 50/125
Compliance	ITU-T G652.D or ISO/IEC 11801 OM3
Minimum bending radius	Not less than 10 times the cable diameter
Peripheral strength element	Steel Tape & E - glass yarn
Color of outer jacket	Black