



NIKOMAX NMC-315DR is designed for simultaneous sealing of several pairs of wires in the 110 type terminal blocks. The tool is a mechanical device designed for the mechanical xation of live wires in the terminals or cross-connect block connector.

The tool is equipped with removable and interchangeable nozzles with impact mechanism. On nozzles are knives for trimming excess lengths of wires after their xation pins. Inserting the knives can be set in the working position or removed with knives inside: easy to x cables, with trimming.

NMC-315DR is packed with 5 pairs intended for terminating multi-pair cables in the 110 type terminal blocks. To seal four pair is more convenient to use with NMC-TA15B nozzle (sold separately). This piece does not crashed into neighboring IDC contacts, help extending their lives, which is especially important for patch panels.

Ordering Table

| P/N | Individual package | | Collective package | | | Freight package | | |
|-----------|--------------------|------------|--------------------|----------------|------------|-----------------|----------------|------------|
| | Dimensions, mm | Weight, kg | Quantity | Dimensions, mm | Weight, kg | Quantity | Dimensions, mm | Weight, kg |
| NMC-315DR | 205x140x24 | 0.465 | 9 pcs. | 300x205x150 | 4.25 | 36 pcs. | 420x320x325 | 18.5 |
| NMC-TA15B | 35x25x25 | 0.052 | 30 pcs. | 220x200x100 | 2.38 | 180 pcs. | 405x235x240 | 10.5 |

Detailed characteristics

| Characteristic | Value |
|------------------------------|--|
| Housing material | High-strength magnesium-aluminum alloy (AL 6061-T6) |
| Warranty | 1 Year |
| Packaging | Individual - Blister pack |
| Color | Black |
| Temperature ranges | Storage from -20 to +70 ° C. Operation from -10 to +50 ° C |
| Additional features | Nozzle for simultaneous closing and trimming of 5 pairs in a set |
| Material of the handle cover | Non-slip thermoplastic (TPR) |
| Shock mechanism | Yes |