



Cable markers are designed for labeling cables, conductors and connections. Marking is performed to ensure that the components differ in their belonging and characteristics.

NIKOMAX Cable markers are made of non-flammable, flexible PVC, resistant to oils and erosion. Markers have a tubular shape with a hollow inner part, which allows you to securely fix the markers on conductors with a diameter of 3.6 to 7.4 mm. In the NIKOMAX product line there are options with both digital (1-9) and lettering (AF).

Ordering Table

P/N	Material	Marking	Color	Volume with packaging, m3	Weight with packaging, kg
NMC-CMR --- YL-500	Polyvinyl chloride	Symbol "-"	Yellow	0.000300	0.120
NMC-CMR-1-YL-500	Polyvinyl chloride	Number 1	Yellow	0.000300	0.120
NMC-CMR-2-YL-500	Polyvinyl chloride	Number 2	Yellow	0.000300	0.120
NMC-CMR-3-YL-500	Polyvinyl chloride	Number 3	Yellow	0.000300	0.120
NMC-CMR-4-YL-500	Polyvinyl chloride	Number 4	Yellow	0.000300	0.120
NMC-CMR-5-YL-500	Polyvinyl chloride	Number 5	Yellow	0.000300	0.120
NMC-CMR-6-YL-500	Polyvinyl chloride	Number 6	Yellow	0.000300	0.120
NMC-CMR-7-YL-500	Polyvinyl chloride	Number 7	Yellow	0.000300	0.120
NMC-CMR-8-YL-500	Polyvinyl chloride	Number 8	Yellow	0.000300	0.120
NMC-CMR-9-YL-500	Polyvinyl chloride	Number 9	Yellow	0.000300	0.120
NMC-CMR-0-YL-500	Polyvinyl chloride	Number 0	Yellow	0.000300	0.120
NMC-CMR-A-YL-500	Polyvinyl chloride	Letter A	Yellow	0.000300	0.120
NMC-CMR-B-YL-500	Polyvinyl chloride	Letter B	Yellow	0.000300	0.120
NMC-CMR-C-YL-500	Polyvinyl chloride	Letter C	Yellow	0.000300	0.120
NMC-CMR-D-YL-500	Polyvinyl chloride	Letter D	Yellow	0.000300	0.120
NMC-CMR-E-YL-500	Polyvinyl chloride	Letter E	Yellow	0.000300	0.120
NMC-CMR-F-YL-500	Polyvinyl chloride	Letter F	Yellow	0.000300	0.120
NMC-CMR-G-YL-500	Polyvinyl chloride	Letter G	Yellow	0.000300	0.120
NMC-CMR-H-YL-500	Polyvinyl chloride	Letter H	Yellow	0.000300	0.120
NMC-CMR-J-YL-500	Polyvinyl chloride	Letter J	Yellow	0.000300	0.120
NMC-CMR-K-YL-500	Polyvinyl chloride	Letter K	Yellow	0.000300	0.120

Detailed characteristics

Characteristic	Value
Temperature ranges	Storage from -40 to +80 ° C. Installation from -40 to +80 ° C. Operation from -40 to +85 ° C.
Warranty	1 year
Marking	A, B, C, D, E, F, G, H, J, K / 0-9 / -
Protection level	Yellow
Permissible diameter of conductors	3.6 - 7.4 mm
Format	Tubular
Packaging	Plastic bag, 10 pcs / roll
Materials	Polyvinyl chloride