



Coupler nylon cable ties - opening, white



Ties are used when laying and installing communication cables and electrical equipment. It is the main way of fixing the cable to trays, brackets and other suitable equipment, provides high strength and reliability of fixation. Ties made of nylon and are designed for installation and operation in the room. The coupler nylon cable ties - opening have a possibility of repeated use due to the special device of the lock mechanism. The use of this type of screed is the most convenient way to cable ties.

## **Ordering Table**

P/N	Length, mm	Width, mm	Color	Pack quantity	Volume with packaging, m3	Weight with packaging, kg
NMC-CTN200-75-F	RL-200	7.5	White	100 pieces.	0.000720	0.230
NMC-CTN250-75-F	RL-250	7.5	White	100 pieces.	0.000900	0.280
NMC-CTN300-75-F	RL-300	7.5	White	100 pieces.	0.001080	0.330
NMC-CTN350-80-RL-350		8.0	White	100 pieces.	0.002240	0.400
NMC-CTN400-80-F	RL-400	8.0	White	100 pieces.	0.003200	0.450



## NMC-CTNxxx-yy-RL-WT-100

Coupler nylon cable ties - opening, white

## **Detailed characteristics**

Characteristic	Value
Туре	Opening
Temperature ranges	Storage from -40 to +80 °C. Installation from 0 to +80. Operation from 0 to +80 °C
Warranty	1 year
Protection level	White
Materials	Nylon PA66
Length	200, 250, 300 mm / 350, 400 mm
Width	7.5 mm / 8.0 mm