

## NMC-KJSE2-ET-MT

Essential Series keystone jack , Shielded, Toolless, 180 degrees, Category 6



NIKOMAX Keystone jacks are designed for installation in faceplates, surface mounting boxes and modular patch panels. Keystone jacks are widely used for connection workplaces to local network.

NIKOMAX Essential keystone jacks («ET» series) are the new design that provides the solution of 180 degrees toolless. This series keystone jacks work together with NIKOMAX full series of cables, patch cords, and patch panels as well. The Toolless design requires no punch down tool, so the termination of keystone jacks will become easier.

### Ordering Table

P/N	Cat.	Type.	Individual package		Freight package		
			Volume, m3	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-KJSE2-ET-M6		Shielded.	-	-	250 pcs.	530x310x230	-

## Detailed characteristics

Characteristic	Value
Category	6
Bandwidth, MHz	250
Connection style	Fully shielded
Compliance	Exceeds the requirements of the standards: ISO / IEC 11801, EN 50173 and ANSI / TIA -568-C.2
Supported applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 10G-BASE-T (For Cat. 6 & 6A), ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C
Warranty	1 year
Connector type	RJ45/8P8C
Connector material in connector	Phosphor bronze
Contact coating material	Gold (50 micro-inches)
Number of cable connections	Not less than 750
Type of IDC contacts (seal)	180 degrees - Toolless
Layout diagram	T568A/B
Installation	Patch panels, surface mount box, faceplate
Protection level	Metallic
Permissible diameter of conductors	~22-26 AWG (0.40-0.60 mm)
Dimensions (WxHxD), mm	16.2 x 21.9 x 28.2
Packaging	Individual - Plastic bag