

NMC-OKxxxH-1U-BK-2



Cable management panel with metal rings, 40mm, 60mm, 80mm

Cable management panel are designed for laying the excess length of patch or hardware cords, which allows you to arrange their placement, avoid loops and ensure good visibility of the marking elements. The consequence of this is the reliability of the system and the simplicity of its maintenance.

NIKOMAX NMC-OKxxxH-1U-BK-2 cable management panel consist of a metal base on which metal rings are mounted. Organizers are supplied with rings of three different sizes: 40, 60 and 80 mm deep.

Ordering Table

| P/N | Depth of rings, | Individual package | | | Freight package | | |
|---------------|-----------------|--------------------|----------------|------------|-----------------|----------------|--------------|
| | mm | Quantity | Dimensions, mm | Weight, kg | Quantity | Dimensions, mn | n Weight, kg |
| NMC-OK400H-1L | J-I40 | 2pcs. | 505x115x50 | 0.9 | 40pcs. | 520x295x450 | 20 |
| NMC-OK600H-1L | J-160 | 2pcs. | 505x115x50 | 0.91 | 40pcs. | 520x295x450 | 20.2 |
| NMC-OK800H-1L | J-180 | 2pcs. | 505x115x50 | 1.0 | 40pcs. | 520x295x590 | 22 |



NMC-OKxxxH-1U-BK-2

Cable management panel with metal rings, 40mm, 60mm, 80mm

Detailed characteristics

| Characteristic | Value |
|--------------------------------------|---|
| Warranty | 1 year |
| Installation | 19" Cabinet or Rack |
| Protection level | Black |
| Packaging | Each Cardboard box, 2 pcs. |
| Height | 10 |
| Material of the supporting structure | Metal |
| Temperature range | Storage from -40 to +70 $^{\circ}$ C. Installation from 0 to +50 $^{\circ}$ C. Operation from -10 to +60 $^{\circ}$ C |
| Number of rings | 5 |
| Depth of rings | 40 mm / 60 mm / 80 mm |
| Material of rings | Metal |