

NMC-PL3PM-WT

Wall-mounted faceplate for 3 inset, Mosaic, 45x45 mm



NIKOMAX Wall-mounted faceplates are designed to install inserts for modules such as Keystone to organize information ports in the workplace, as well as to install other mechanisms compatible with the French standard Mosaic (45x45 mm).

The front panels NMC-PL1PM-WT, NMC-PL2PM-WT and NMC-PL3PM-WT hold 1, 2 or 3 inserts of Mosaic format 45x45 mm, respectively. At the base of the panels there are metal subframes for mounting on the mounting boxes and coasters with an interaxial distance between the screws of 60 mm. The outreach of the front frame with respect to the subframe can be adjusted within up to 3 millimeters.

Ordering Table

| P/N | Number of | Individual package | | Collective package | | Freight package | | | |
|------------|------------|--------------------|------------|--------------------|-------------------|-----------------|----------|-------------------|------------|
| | sockets | Volume, m3 | Weight, kg | Quantity | Dimensions, mm | Weight, kg | Quantity | Dimensions, mm | Weight, kg |
| NMC-PL3PM- | V3x Mosaic | 0.000498 | 0.105 | 20 pcs. | 250x190x210 | 2.4 | 80 pcs. | 515x400x230 | 9.9 |



NMC-PL3PM-WT

Wall-mounted faceplate for 3 inset, Mosaic, 45x45 mm

Detailed characteristics

| Characteristic | Value |
|---|---|
| Temperature ranges | Storage from -40 to +70 $^{\circ}$ C. Installation from 0 to +50 $^{\circ}$ C. Operation from -10 to +60 $^{\circ}$ C |
| Individual packing | Plastic bag |
| Warranty | 1 year |
| Plastic material | Meets UL94V-0 |
| Installation | Wall-mounted, with metal subframe |
| Protection level | White |
| Number of sockets | 3 |
| Type of inserts to be installed | Mosaic 45x45 mm or 22.5x45 mm |
| Dimensions (on the front side, WxHxD), mm | 240x80x8 |