



NIKOMAX Wall-mounted socket are designed to install inserts for modules such as Keystone to organize information ports in the workplace, as well as to install other mechanisms compatible with the British standard (50x50 mm).

The wall-mounted socket hold 1,2 and 3 insert of British format 50x50 mm, respectively. At the base of the panels there are metal subframes for mounting.

NMC-PL80x80-1PA-WT - NIKOMAX wall-mounted socket 1 port, for Keystone insert modules, white.

NMC-PL80x80-2PA-WT - NIKOMAX wall-mounted socket 2 port, for Keystone insert modules, white.

NMC-PL80x80-3PA-WT - NIKOMAX wall-mounted socket 3 port, for Keystone insert modules, white.

### Ordering Table

P/N	Number of ports	Dimensions, mm	Individual package	
			Volume, m3	Weight, kg
NMC-PL80X80-1PA-WT	1	80x80x22.14	-	-
NMC-PL80X80-2PA-WT	2	80x80x22.14	-	-
NMC-PL80X80-3PA-WT	3	80x80x22.14	-	-

**Detailed characteristics**

<b>Characteristic</b>	<b>Value</b>
Temperature ranges	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C
Warranty	1 year
Number of ports	1 / 2 / 3
Plastic material	Meets UL94V-0
Installation	Wall-mounted
Protection level	White
Dimensions (WxHxD), mm	80x80x22.14 mm
Packaging	Individual - plastic bag
Type of inserts to be installed	British 50x50 mm