



RJ45/8P8C plugs are designed for termination of solid (single-core) and stranded (patch cord) cables in production of patch cords and in some cases while laying communication lines, for connecting CCTV cameras, etc.

NIKOMAX Self-clamping Field Toolless Plugs are designed specifically for use with high-speed cables and provide first-class transmission characteristics. Connectors can be used to stack server hardware, workstations, connect various specialized industrial equipment and CCTV cameras.

NMC-RJ88UE2-NT-GY (Cat.6) connector is made in cast, unshielded plastic, complies with UL94V-0. They consist of a central insert with RJ45 plug and PCB with IDC, the body divided into two halves and a plastic shank for cable fixation. The supported thickness of the outer shell is 6-8 mm.

Connectors design makes it easy to plug the cables without any specialized tools. Only diagonal cutters are needed to gently bite off excess wires.

Supplied individually, in an individual polyethylene bag with perforation – similar to switching modules.

Ordering Table

P/N	Category	Type	Individual Package		Group Package		Transport Package			
			Volume, m3	Weight, kg	Quantity	Size, mm	Weight, kg	Quantity	Size, mm	Weight, kg
NMC-RJ88UE6		Unshilded	0,000169	0,018	70	250x190x210	1,26	280	515x400x230	6,0

Detailed characteristics

Characteristic	Value
Category	6
Bandwidth, MHz	250
Connection style	Unshielded
Supported applications	10BASE-T, 100BASE-TX, 100BASE-T4. 1000BASE-T, 10G-BASE-T, ATM-25. ATM-51. ATM-155. 100VG-AnyLan, TR-4. TR-16 Active, TR-16 Passive
Temperature ranges	Storage from -20 to +60 °C. Installation from 0 to +50 °C. Operation from -20 to +60 °C
Warranty	1 year
Contact coating material	Gold (50 µinch)
Number of cable connections	750 cycles minimum
Type of IDC contacts (seal)	Toolless
Layout diagram	T568A/B
IDC Contact material	Phosphor bronze
IDC coating material	Tin (100 µinch)
Protection level	Grey
Insulation resistance	min. 500 MΩ (with 100 V DC)
Maximum load-bearing capacity	1000 V for 1 minute (DC, 60 Hz)
Permissible diameter of conductors	~24-23 AWG (0,500-0,585 mm)
Housing material	Plastic, complies with UL94V-0
Dimensions (WxHxD), mm	55,3x15,0x13,8
Supported cable diameter	6-8 mm
Connector type	RJ45/8P8C
Material of contacts	Phosphor bronze
Packaging	Individual – PE bag
Compliance	Exceeds the requirements of the standards: ISO/IEC 11801. EN 50173 & TIA/EIA-568-C.2