



Modular Patch Panels are designed for connecting different SCS subsystems and network equipment to each other with patch cords.

NIKOMAX NMC-RP24-BLANK-1U-MT has a standard height of 1U and 24 nests for Keystone jacks. The modular design is extremely easy to install and allows the flexibility to combine different types of connectors and categories on a single frame. If required, the jack can easily be removed and rearranged to another port or panel. All ports of panel are numbered and have additional labeling area.

The patch panel is made of 1.5 mm steel and is suitable for both shielded and unshielded jacks. For better shielding against electromagnetic interference and improve communication with unpainted rails cabinet, galvanized steel panels coated with nickel.

The patch panels offer convenient detachable organizers for routing incoming cables.

### Ordering Table

P/N	Number of ports	Height, U	Individual package		Freight package		
			Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-RP24-BLANK24		1	510x80x60	0.8	15 pcs.	515x400x230	13.1

**Detailed characteristics**

<b>Characteristic</b>	<b>Value</b>
Connection style	Shielded
Temperature ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating -10 to +60 ° C
Individual packing	Cardboard box
Warranty	1 year
Number of ports	24
Height, U	1
Marking	All ports are numbered, there are additional labeling area
Installation	19 " Cabinet or rack
Protection level	Metallic (Nickel)
Housing material	Nickel-plated steel, 1.5 mm
Type of installed modules	Keystone (no wider than 17mm)
Depth in rack (with organizer), mm	157