

NMC-RP24-BLANK-AN-1U-MT

Patch Panel, with Angled Jacks, 1U



Patch Panels are designed for connecting different SCS subsystems and network equipment to each other with patch cords.

NIKOMAX NMC-RP24-BLANK-AN-1U-MT has a standard height of 1U and 24 ports for NIKOMAX angled jacks Series AN (Panel is compatible with any standard keystone jacks).

A feature AN series module is with an angled design allows you to conveniently lay patch cords to the side and fasten them to the vertical cable organizer. This solution eliminates the need for standard cable shunting rings, saving valuable space in the cabinet.

The patch panel is made of 1.5 mm steel and is suitable for both shielded and unshielded jacks. For better shielding against electromagnetic interference and improve communication with unpainted rails cabinet, galvanized steel panels coated with nickel.

The patch panels offer removable organizers for routing incoming cables.

Ordering Table

P/N	Number of ports	Height, U	Individual package		Freight package		
			Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-RP24-BLANK24		1	510x80x60	0.8	15 pcs.	515x400x230	13.1

Detailed characteristics

Characteristic	Value
Connection style	Shielded
Temperature ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating -10 to +60 ° C
Individual packing	Cardboard box
Warranty	1 year
Number of ports	24
Height, U	1
Marking	All ports are numbered, there are additional labeling area
Installation	19" Cabinet or rack
Protection level	Metallic (Nickel)
Housing material	Nickel-plated steel, 1.5 mm
Type of installed modules	Keystone (no wider than 17 mm)
Depth in rack (with organizer), mm	88