

# NMC-RP24U-BLANK-ST-1U-BK

Modular Patch Panel, UTP, 1U



Modular Patch Panels are designed for connecting different SCS subsystems and network equipment to each other with patch cords.

NIKOMAX **NMC-RP24S-BLANK-ST-1U-BK** has a standard height of 1U and 24 ports for Keystone jacks. The modular design is extremely easy to install and allows the flexibility to combine different types of connectors and categories on a single frame. If required, the jack can easily be removed and rearranged to another port or panel. All ports of panel are numbered and have additional labeling area. The patch panels offer convenient detachable organizers for routing incoming cables

## Ordering Table

P/N	Type	Ports	Height,U (mm)	Dimensions, mm	Weight, kg
NMC-RP24U-BLANK-ST-1U-BK	Unshielded	24	1U	518x125x50	-

**Detailed characteristics**

<b>Characteristic</b>	<b>Value</b>
Connection style	Unshielded
Temperature ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating -10 to +60 ° C
Individual packing	Cardboard box
Warranty	1 year
Number of ports	24
Height, U	1
Marking	All ports are numbered, there are additional labeling area
Installation	19 " Cabinet or rack
Housing material	Plastic and steel
Type of installed modules	Keystone