


**NMF-CJ12M3PA-MTPM-LCU-1S**

Pre-terminated optical cassette module, 12 ports LC / UPC, MM 50/125, OM3



Cassette modules are designed exclusively for mounting in NIKOMAX NMC-RP08-BLANK-CJ-1U-MT patch panel.

Optical cassettes are made in plastic translucent casings and as ready-made pre-terminated solutions with a capacity of 12 LC or SC ports. Inside the cassette there is a cable assembly of Hydra fan-out: 1x MTP Male (Premium) on 12x SC or LC connectors.

**Ordering Table**

P/N	Size, slot	Fiber type	Outgoing Connectors		Weight, kg
			Quantity	Type/polish	
NMF-CJ12M3PA-MTPM-11		MM 50/125 OM3	12	LC / UPC	0.14

**Detailed characteristics**

<b>Characteristic</b>	<b>Value</b>
Warranty	1 year
Packaging	Cardboard box
Type of optical fiber	Multimode fiber 50/125 (MM)
Class of fiber	OM3
Insertion loss	≤ 0.25 dB - for LC connector ≤ 0.1 dB - for the MTP connector
Return loss	≥ 60 dB - for LC connector ≥ 60 dB - for the MTP connector
Number of Front Ports	12
The ports are front. / Polishing	LC / UPC
Cassette size, slot	1
Port rear / polished	MTP Elite - Male / UPC
Polarization	Type A
Jacket Casing Material	LSZH
Diameter of the cords	0.9 mm
Color of Fiber Optic cable shell	Blue, orange, green, brown, gray, white, red, black, yellow, purple, lilac, aqua
Cassette material	Plastic
Cassette color	Blue, translucent
Temperature range	Storage from -20 to +65 ° C. Operation -5 to +65 ° C