

NMF-PC1M4C2-SCU-SCU-xxx



Fiber Optic Patch Cord, MM 50/125, OM4, SC/UPC-SC/UPC, LSZH, Simplex

Fiber optic patch cords are designed to connect various segments of optical network cables, as well as to connect them to active network switches and patch panels. Patch cords provide high reliability of connection and allowing for re-connection quickly. Fiber optic patch cords are a piece of optical cable terminated on both sides by SC, LC, FC, ST connector types with UPC or APC polishing type. Patch cords can be manufactured using single-mode or multimode fiber. Availble in OM2, OM3, OM4 fiber class types. Optical cords are divided into Simplex and Duplex according to the type of performance, duplex cords are marked with «polarity» connectors, through which users can determine from which connector the light comes out. Outer jacket is color coded to differentiate multimode or single-mode.

Ordering Table

P/N	Connection style	Connector Type	Polishing	Length, m	Individual package	
					Volume, m3	Weight, kg
NMF-PC1M4C2-SCU-Simplex		SC-SC	UPC	1	-	0.01
NMF-PC1M4C2	2-SCU-Simplex	SC-SC	UPC	2	-	0.02
NMF-PC1M4C2	2-SCU-Simplex	SC-SC	UPC	3	-	0.02
NMF-PC1M4C2	2-SCU-Simplex	SC-SC	UPC	5	-	0.03
NMF-PC1M4C2	2-SCU-Simplex	SC-SC	UPC	10	=	0.04
NMF-PC1M4C2	2-SCU-Simplex	SC-SC	UPC	15	_	0.06



NMF-PC1M4C2-SCU-SCU-xxx

Fiber Optic Patch Cord, MM 50/125, OM4, SC/UPC-SC/UPC, LSZH, Simplex

Detailed characteristics

Characteristic	Value
Outer jacket material	LSZH
Warranty	1 year
Packaging	Plastic bag
Temperature ranges	Storage from -20 to +65 ° C. Operation -5 to +65 ° C
Type of optical fiber	Multimode 50/125
Type of cable	Patch Cord
Class of fiber	OM4
Connectors / Polishing	SCU-SCU
Diameter of outer jacket, mm	2
Color of outer jacket	Magenta
Insertion loss	≤ 0.3 dB
Return loss	≥ 50 dB