

NMF-RP24SC-TS-P-1U-BK

■Fiber Distribution Unit 19", 1U, for 24 Simplex SC adapters or 48 Simplex LC adapters, sliding type, with shelf, black

Rack Mount Fiber Distribution Unit (FDU) are designed for switching optical fibers, in particular to create a detachable connection between optical cords connected to active equipment and terminated with fiber optic cables. Optical cables are built into the FDU and terminated with the necessary connectors by welding with pigtails. To protect the joints and lay the stocks of fiber lengths, special splice cassettes and heat shrink sleeves are used. The connection of the terminated cable to the patch cords takes place through the optical pass-through adapters, which are installed in the removable panels on the front part of the FDU. Rack Mount Fiber Distribution Unit (FDU) **NMF-RP24SC-TS-P-1U-BK** is designed for mounting in a switching 19" cabinet or rack. FDU body is made of steel and reliably protects fibers from external mechanical impact and foreign objects getting inside. FDU has 4 cable entries on the rear wall and, accordingly, 4 nodes for mounting cable. A feature of this FDU is a retractable design that provides easy access to the contents of the FDU. There is also a front shelf and inside the FDU for convenience, the organizer is located.

Ordering Table

P/N	Color	Number of ports	Individual package	
			Volume, m3	Weight, kg
NMF-RP24SC-TS-P-1U-BK	Black	24 SC / 48 LC	-	-

■Fiber Distribution Unit 19", 1U, for 24 Simplex SC adapters or 48 Simplex LC adapters, sliding type, with shelf, black

Detailed characteristics

Characteristic	Value
Type	Extendable with front shelf
Protection level	Black
Packaging	Individual - Cardboard box
Temperature ranges	Storage from -20 to +65° C. Operation from -20 to +65° C
Number of ports for main cables	1 year
Material	Steel 1.2 mm
Capacity, max	12 mm
Possibility of splitter installation	24 Simplex SC / 48 Simplex LC / 24 Duplex LC
Outside dimension (LxWxH)	19 "Rack or Cabinet
Type of adapter	Simplex SC / Duplex LC