

NMF-RP24SC-TS-P1-1U-BK



■Fiber Distribution Unit 19", 1U, for 24 Simplex SC adapters or 48 Simplex LC adapters, sliding type, with shelf, black, splice - cassette, KDZS sleeves

Rack Mount Fiber Distribution Unit (FDU) are designed for switching optical fibers, in particular to create a detachable connection between optical cords connected to active equipment and terminated with fiber optic cables. Optical cables are built into the FDU and terminated with the necessary connectors by welding with pigtails. To protect the joints and lay the stocks of fiber lengths, special splice cassettes and heat shrink sleeves are used. Rack Mount Fiber Distribution Unit (FDU) **NMF-RP24SC-TS-P1-1U-BK** is designed for mounting in a switching 19" cabinet or rack. FDU body is made of steel and reliably protects fibers from external mechanical impact and foreign objects getting inside. FDU has 4 cable entries on the rear wall and, accordingly, 4 nodes for mounting cable. A feature of this FDU is a retractable design that provides easy access to the contents of the FDU. The retractable section has a standard design, it is a metal tray (with installed components) on telescopic guides. To fix the retractable section, plastic clips are provided, the counterpart for which is located on the chassis of the FDU.

Ordering Table

P/N	Color	Number of ports	Individual package	
			Volume, m3	Weight, kg
NMF-RP24SC-TS-P1-1U-BK	Black	24 SC/48 LC	0.007778	3.870

■Fiber Distribution Unit 19", 1U, for 24 Simplex SC adapters or 48 Simplex LC adapters, sliding type, with shelf, black, splice - cassette, KDZS sleeves

Detailed characteristics

Characteristic	Value
Maximal number of ports	24 SC / 48 LC
Maximal cable diameter, mm	12
Number of cable entries	4
Installation	19 "Rack or Cabinet
Dimensions (LxWxH), mm	482x250x44 (without shelf) / 482x312x44 (with shelf)
Type	Extendable with front shelf
Color	Black
Packaging	Individual - Cardboard box
Temperature ranges	Storage from -20 to +70° C. Operation from -20 to +60° C
Warranty	1 year
Material	Steel 1.2 mm