



## NMF-SC-1V-48-4MS

Splice Closure, 48 fibers, 4 round ports, with 4pcs. of splice tray, with standard accessories, mechanical sealing

Optical splice closure NMF-SC-1V-48-4MS is designed to be placed on cable and railway contact network supports, walls of buildings and structures. The possibility of branching and branching of passing trunk lines, including without opening some modules, has been implemented.

The cable entries are sealed with three gaskets of various materials and sealing tape, then tightened with a special nut. This solution provides moisture and dust insulation of cable entries.

The body of the splice closure is made of impact-resistant frost-resistant polycarbonate and a special sealing system provides long-term and reliable protection of splices. They are distinguished by a reinforced casing and the presence of special hinges on the cover for mounting on the suspension in a horizontal position.

### Ordering Table

P/N	Number of cable entries	Max. Cable diameter	Volume with packaging	Weight with packaging
NMF-SC-1V-48-4MS	4 round inputs	4 x 13 mm	-	-

NMF-SC-1V-48-4MS

Splice Closure, 48 fibers, 4 round ports, with 4pcs. of splice tray, with standard accessories,  
mechanical sealing

Detailed characteristics

Characteristic	Value
Packaging	Individual - Cardboard Box
Temperature range	Operation from - 50C to + 70C
Dimensions (L x W)	415 x Ø157 mm
Protection level	IP65
Maximum cable diameter	4 x 13 mm
Weight, kg	2.2 kg
Maximum number of splices	48
Number of cable entries	4 round inputs