

NMF-SC-2V-144-5HS

Splice Closure, 144 fibers, 4 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo hermetic sealing

Optical splice closure NMF-SC-2V-144-5HS is designed to be fixed on the supports of overhead cable lines, walls of buildings and structures. It is advantageous to use small capacitance couplings in places of broaching peripheral communication lines and in places of branches of peripheral lines to subscriber lines. Recommended for places with high humidity and high content of dust in the air.

The "hot" method of assembling and sealing cable glands with heat shrinkable tubing increases the strength of the cable fixation system, the anti-vandal resistance of the coupling and ensures absolute isolation from dust and moisture. The body is made of impact-resistant frost-resistant polycarbonate.

Ordering Table

P/N	Number of cable entries	Max. Cable diameter	Volume with packaging	Weight with packaging
NMF-SC-2V-144-5HS	4 round & 1 oval	4 x 20 mm / 1 x 40 mm	-	-

Splice Closure, 144 fibers, 4 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo hermetic sealing

Detailed characteristics

Characteristic	Value
Packaging	Individual - Cardboard Box
Temperature range	Operation from - 50C to + 70C
Dimensions (L x W)	500 x Ø189 mm
Protection level	IP68
Maximum cable diameter	4 x 20 mm / 1 x 40 mm
Weight, kg	2.4 kg
Maximum number of splices	144
Number of cable entries	4 round & 1 oval inlet/outlet