



NMF-SC-2V-48-4HS

Splice Closure, 48 fibers, 3 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo hermetic sealing metal hoop

Optical splice closure NMF-SC-2V-48-4HS is designed to be fixed on the supports of overhead cable lines, walls of buildings and structures. It is advantageous to use small capacitance couplings in places of broaching peripheral communication lines and in places of branches of peripheral lines to subscriber lines. Recommended for places with high humidity and high content of dust in the air.

The clutch is equipped with a special mechanical locking system in the form of two semi-braids with a lock, fixed by a special bolt, which greatly facilitates the assembly of the clutch, as well as access to the clutch during maintenance and repair.

The "hot" method of assembling and sealing cable glands with heat shrinkable tubing increases the strength of the cable fixation system, the anti-vandal resistance of the coupling and ensures absolute isolation from dust and moisture. The body is made of impact-resistant frost-resistant polycarbonate.

Ordering Table

P/N	Number of cable entries	Max. Cable diameter	Volume with packaging	Weight with packaging
NMF-SC-2V-48-4HS	4 (3 round + 1 ellipse)	3 x 16 mm / 1 x (25 x 44) mm	-	-

Splice Closure, 48 fibers, 3 round & 1 oval port, with 4 pcs. of splice tray, with standard accessories, thermo hermetic sealingmetal hoop

Detailed characteristics

Characteristic	Value
Protection level	IP68
Packaging	Individual - Cardboard Box
Temperature range	Operation from - 50C to + 70C
Dimensions (L x W)	435 x Ø157 mm
Maximum cable diameter	3 x 16 mm / 1 x (25 x 44) mm
Weight, kg	1.8 kg
Maximum number of splices	48
Number of cable entries	4 (3 round + 1 ellipse)