

## **NMR-BRSH-F-XX**

Brush entry for NIKOMAX floor cabinets



The brush entries NMR-BRSH-F-GY, NMR-BRSH-F-BK are intended to protect installed equipment from dust, small objects, mechanical damage of the cable-sheath, which is introduced into the cabinet through the brush entry. The product consists of a plastic body, in which bristles of black polypropylene are fixed. The cable is pulled through the bristles. The brush entry is intended to be installed in special places in the foundation and roof of the cabinet.

## **Ordering Table**

P/N Color	Individual pa	Individual package		Group package		
	Quantity	y Dimensions, mm	n Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMR-BRSH-F-GY Grey	1 pc.	190x70x5	0.06	50 pcs.	520x520x100	3.00
NMR-BRSH-F-BK Black	1 pc.	190x70x5	0.06	50 pcs.	520x520x100	3.00



## NMR-BRSH-F-XX

Brush entry for NIKOMAX floor cabinets

## **Detailed characteristics**

Characteristic	Value
Depth, mm	70
Installation envelope, mm	350
Weight, kg	0.05
Type of cabinet for intallation	Floor-mounted
Width, mm	370
Coating	Powder, polymeric-epoxy
Protection level	Grey / Black
Height	8 mm
Materials	Steel sheets (1.0 mm)
Bristles opening size, mm	340 x 56
Fastener Assembly	Screw x 2pcs. (3.3 x 6 mm)