

NMR-SHFS-XXX-GY

NIKOMAX Fixed shelf for wall and floor cabinets NMR-series, thickness 1.2 mm, grey



Fixed shelf is made of sheet steel. The surface of the shelf is perforated for better ventilation of equipment. Mounting is carried out at four points on the side surfaces of perforated profiles It is intended to be used for to install and support heavy equipment in wall and floor telecommunication cabinets NIKOMAX NMR-series in accordance with the accessories compatibility table.

Ordering Table

| P/N | Installation type | Shelves width, mm | Shelves depth, mm | Depth of installation for cabinet | Package size, HxWx mm | D, Volume, m3 | Weigh, kg |
|------------|---------------------|-------------------|-------------------|-----------------------------------|--------------------------|---------------|-----------|
| NMR-SHFS-V | V45-CWall-mounted | 489 | 275 | 450 | 60x530x300 | 0.000954 | 2.0 |
| NMR-SHFS-V | V60-CWall-mounted | 489 | 425 | 600 | 60x550x450 | 0.01485 | 2.6 |
| NMR-SHFS-F | 60-G'Floor-standing | 472 | 350 | 600 | 60x370x520 | 0.01154 | 2.2 |
| NMR-SHFS-F | 80-G'Floor-standing | 472 | 550 | 800 | 60x590x480 | 0.01699 | 3.4 |



NMR-SHFS-XXX-GY

NIKOMAX Fixed shelf for wall and floor cabinets NMR-series, thickness 1.2 mm, grey

Detailed characteristics

| Characteristic | Value |
|---------------------------------|-------------------------------|
| Depth L, mm | 275 / 425 / 350 / 550 |
| Installation size L1, mm | 175 / 325 / 250 / 450 |
| Weight, kg | 2.0 / 2.1 / 2.3 / 4.1 |
| Type of cabinet for intallation | Wall / Floor |
| Width, mm | 489 / 472 |
| Coating | Powder, polymer-epoxy, grey |
| Material | Cold rolled steel sheet 1.2mm |
| Height | 48 mm |
| Maximum load-bearing capacity | 100 kg |