

NIKOMAX Wall-mounted socket are designed to install inserts for modules such as Keystone to organize information ports in the workplace, as well as to install other mechanisms compatible with the British standard (50x50 mm).

The wall-mounted socket hold 1,2 and 3 insert of British format 50x50 mm, respectively. At the base of the panels there are metal subframes for mounting.

NMC-PL80x80-1PA-WT - NIKOMAX wall-mounted socket 1 port, for Keystone insert modules, white.

NMC-PL80x80-2PA-WT - NIKOMAX wall-mounted socket 2 port, for Keystone insert modules, white.

NMC-PL80x80-3PA-WT - NIKOMAX wall-mounted socket 3 port, for Keystone insert modules, white.



NMC-PL80x80-1PA-WT
for 1 ports



NMC-PL80x80-2PA-WT
for 2 ports



NMC-PL80x80-3PA-WT
for 3 ports

Package Content

	NMC-PL80x80-1PA-WT	NMC-PL80x80-2PA-WT	NMC-PL80x80-3PA-WT
Bracket	1 pcs	1 pcs	1 pcs
Plate	1 pcs	1 pcs	1 pcs
Bezel	1 pcs	1 pcs	1 pcs
Shutter door	1 pcs	2 pcs	3 pcs
Screw	1 pcs	1 pcs	1 pcs
Window	1 pcs	1 pcs	1 pcs

Specification

	NMC-PL80x80-1PA-WT	NMC-PL80x80-2PA-WT	NMC-PL80x80-3PA-WT
Number of ports	1	2	3
Type of inserts to be installed	British 50x50 mm		
Plastic material	Meets UL94V-0		
Color	White		
Installation	Wall-mounted		
Dimensions (on the front side), WxHxD	80x80x22,14 mm		
Temperature ranges	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C		
Warranty	1 year		
Packaging	Individual - plastic bag		

