

NMC-CB110-50NL - without legs
NMC-CB110-100NL - without legs
NMC-CB110-50L - with legs
NMC-CB110-100L - with legs
110 type wall-mounted switching unit

110 type crosses are used for cutting cables of various SCS subsystems on them.

- ✓ Impact resistant and non flammable plastic
- ✓ Plastic conforms to UL 94V-0
- ✓ Marks are applied every 5 pairs for wiring easily

The main advantage is patch each individual pair, providing high flexibility in cabling reconfiguration. Connection and switching is carried out using 110 type connectors or appropriate patch cords. The breakout boxes are usually wall-mounted and come in two configurations, with and without built-in plastic mounting feet. The option with legs provides more convenient cable routing. To work more conveniently with 110 blocks, labels are applied to the mounting grooves every 5 pairs. The leg units are also labeled with removable transparent holders.

Switching units **NMC-CB110-50L** and **NMC-CB110-50NL** have 50 pairs, and **NMC-CB110-100L** and **NMC-CB110-100NL** have 100 pairs. For sealing 110 panels, blocks and connectors, it is recommended to use the **NMC-315DR** tool for sealing of several pairs simultaneously (4 or 5, depending on the nozzle). It facilitates greatly and speeds up the work.



NMC-CB110-50NL



NMC-CB110-100NL



NMC-CB110-50L



NMC-CB110-100L

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties.

Basic equipment :

| | |
|-------------------------------|------------|
| Switching units | 1 pc |
| Label for marking (with legs) | 1 or 2 pcs |

Specification

| Product Number | NMC-CB110-50NL | NMC-CB110-100NL | NMC-CB110-50L | NMC-CB110-100L |
|--------------------|---|-----------------|---------------|----------------|
| Type | Without legs | | With legs | |
| Temperature ranges | Storage from -40 to +70 °C. Installation from 0 to +50 °C. Operation from -10 to +60 °C | | | |
| Warranty | 1 year | | | |
| Number of ports | 50 | 100 | 50 | 100 |
| Plastic material | Conforms to UL 94V-0 | | | |
| Marking | Every 5 pairs | | | |
| Installation | Wall | | | |
| Color | White | | | |
| Packaging | Individual - cardboard box, 10 pcs | | | |

Order Table

| Product Number | Number of pairs | Type | Individual packaging | | Group packing | | | Transport packaging | | |
|-----------------|-----------------|--------------|----------------------|------------|---------------|----------------|------------|---------------------|----------------|------------|
| | | | Volume, m3 | Weight, kg | Quantity | Dimensions, mm | Weight, kg | Quantity | Dimensions, mm | Weight, kg |
| NMC-CB110-50NL | 50 | Without legs | 0.00036 | 0.087 | 45 pcs | 240x290x240 | 4.3 | 180 pcs | 490x490x300 | 18.1 |
| NMC-CB110-100NL | 100 | Without legs | 0.00127 | 0.174 | 19 pcs | 240x290x240 | 4 | 76 pcs | 490x490x300 | 16.6 |
| NMC-CB110-50L | 50 | With legs | 0.00086 | 0.115 | 6 pcs | 280x100x280 | 1 | 60 pcs | 580x530x300 | 10.2 |
| NMC-CB110-100L | 100 | With legs | 0.00254 | 0.23 | 3 pcs | 280x100x280 | 1.1 | 30 pcs | 580x530x300 | 10.8 |

Related Prodducts :

Connectors 110: NMC-CC110UD4-100, NMC-CC110UD5-100

110 type breakout plugs: NMC-CP110UD1-WT-50, NMC-CP110UD2-WT-50, NMC-CP110UD4-WT-50

Patch cords 110

Multipair impact punch down tool: NMC-315DR

Impact punch down tool: NMC-3640R

Cable stripper: NMC-S501B

Blades for punch-down tools: NMC-14TA, NMC-14TBK

Non-opening nylon ties: TCT-CVXXX-ZZ

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties.