

**NMC-CB110-50NL** - without legs  
**NMC-CB110-100NL** - without legs  
**NMC-CB110-50L** - with legs  
**NMC-CB110-100L** - with legs  
110 type wall-mounted switching unit

110 type crosses are used for cutting cables of various CKC subsystems on them.

- ✓ Impact resistant and non flammable plastic
- ✓ Plastic conforms to UL 94V-0
- ✓ Marks are applied every 5 pairs for wiring easily

The main advantage is patch each individual pair, providing high flexibility in cabling reconfiguration. Connection and switching is carried out using 110 type connectors or appropriate patch cords. The breakout boxes are usually wall-mounted and come in two configurations, with and without built-in plastic mounting feet. The option with legs provides more convenient cable routing. To work more conveniently with 110 blocks, labels are applied to the mounting grooves every 5 pairs. The leg units are also labeled with removable transparent holders.

Switching units **NMC-CB110-50L** and **NMC-CB110-50NL** have 50 pairs, and **NMC-CB110-100L** and **NMC-CB110-100NL** have 100 pairs. For sealing 110 panels, blocks and connectors, it is recommended to use the **NMC-315DR** tool for sealing of several pairs simultaneously (4 or 5, depending on the nozzle). It facilitates greatly and speeds up the work.



**NMC-CB110-50NL**



**NMC-CB110-100NL**



**NMC-CB110-50L**



**NMC-CB110-100L**

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties.

**Basic equipment :**

Switching units	1 pc
Label for marking (with legs)	1 or 2 pcs

**Specification**

Product Number	NMC-CB110-50NL	NMC-CB110-100NL	NMC-CB110-50L	NMC-CB110-100L
Type	Without legs		With legs	
Temperature ranges	Storage from -40 to +70 °C. Installation from 0 to +50 °C. Operation from -10 to +60 °C			
Warranty	1 year			
Number of ports	50	100	50	100
Plastic material	Conforms to UL 94V-0			
Marking	Every 5 pairs			
Installation	Wall			
Color	White			
Packaging	Individual - cardboard box, 10 pcs			

**Order Table**

Product Number	Number of pairs	Type	Individual packaging		Group packing			Transport packaging		
			Volume, m3	Weight, kg	Quantity	Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-CB110-50NL	50	Without legs	0.00036	0.087	45 pcs	240x290x240	4.3	180 pcs	490x490x300	18.1
NMC-CB110-100NL	100	Without legs	0.00127	0.174	19 pcs	240x290x240	4	76 pcs	490x490x300	16.6
NMC-CB110-50L	50	With legs	0.00086	0.115	6 pcs	280x100x280	1	60 pcs	580x530x300	10.2
NMC-CB110-100L	100	With legs	0.00254	0.23	3 pcs	280x100x280	1.1	30 pcs	580x530x300	10.8

**Related Prodducts :**

Connectors 110: NMC-CC110UD4-100, NMC-CC110UD5-100

110 type breakout plugs: NMC-CP110UD1-WT-50, NMC-CP110UD2-WT-50, NMC-CP110UD4-WT-50

Patch cords 110

Multipair impact punch down tool: NMC-315DR

Impact punch down tool: NMC-3640R

Cable stripper: NMC-S501B

Blades for punch-down tools: NMC-14TA, NMC-14TBK

Non-opening nylon ties: TCT-CVXXX-ZZ

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties.