

## NMC-KJUD2-IS-PC-BK

NIKOMAX industrial socket modules,  
cat. 5e, RJ45 / 8P8C, 110 / KRONE,  
T568A / B, black

- ✓ Exceeds the requirements of standards: ISO / IEC 11801, EN 50173 and TIA / EIA-568
- ✓ IP67 protection
- ✓ Extended warranty - 5 years

NIKOMAX industrial insert modules with IP67 degree of protection. These modules are designed for termination of fixed cables and made in shielded and unshielded versions and correspond to category 5e. They have universal IDC contacts with additional cutouts to hold the wires during installation.



## NMC-KJUD2-IS-PC-BK

Basic equipment :

Industrial socket modules

1

## Specification

Product Number	NMC-KJUD2-IS-PC-BK
Category	5e
Bandwidth, MHz	250
Diameter of conductors, AWG	~ 24-22 AWG (0.50-0.65 mm)
Execution	Unshielded
Compliance	Exceeds requirements of standards: ISO / IEC 11801, EN 50173 and TIA / EIA-568
Supported applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 10GBASE-T (for Cat.6 and 6A), ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR- 16 Active, TR-16 Passive
Temperature range	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C
Warranty	5 years - extended; 25 years - as part of the certified SCS NIKOMAX
Connector type	RJ45 / 8P8C
Contact cover material in the connector	Phosphor bronze
Contact coating material	Gold (50 mcd) over nickel (100 mcd)
Contact coating material	Tin (100 mcd)
Number of cord connections	Not less than 750
Type of IDC contacts (termination)	Blades 110 / KRONE
Wiring diagram	T568A / B
IDC Contact material	Phosphor bronze
Installation	Termination of fixed cables
Color	White
Insulation resistance	Not less than 500 MOhm (at a constant voltage of 100 V)
Ultimate load capacity	Up to 1000 V, 60 Hz for 1 minute
Contact resistance, μΩ	No greater than 20 μOhm
Packaging	Individual - Plastic bag
Material of base	High strength, non-flammable, conform to UL94V-0
Degree of protection	IP67
Protective part color	Black

## Order Table

Product Number	Category	Type	Individual packaging		Group packing			Transport packaging		
			Volume, m3	Weight, kg	Quantity	Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-KJUD2-IS-PC-BK	5e	UTP	-	-	-	-	-	-	-	-

## Related products :

Twisted Pair Terminator, Impact Type: NMC-3640R

Blades-inserts for NMC-3640R: NMC-14TA, NMC-14TBK

Side cutters: NMC-222

Wire cutters: NMC-502C

Stripper and cutter for cables: NMC-S501B

Tightening and cutting device for nylon ties: NMC-328

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties.