

Patch Panels are designed for connecting different SCS subsystems and network equipment to each other with patch cords.

**NIKOMAX NMC-RP24-BLANK-AN-1U-MT** has a standard height of 1U and 24 ports for NIKOMAX angled jacks Series AN (Panel is compatible with any standard keystone jacks). A feature AN series module is with an angled design allows you to conveniently lay patch cords to the side and fasten them to the vertical cable organizer. This solution eliminates the need for standard cable shunting rings, saving valuable space in the cabinet.

The patch panel is made of 1.5 mm steel and is suitable for both shielded and unshielded jacks. For better shielding against electromagnetic interference and improve communication with unpainted rails cabinet, galvanized steel panels coated with nickel.

There are additional markings area All ports are numbered Removable organizer with a ring for each cables Shielded, nickel-plated housing Grounding wire grounding on common bus NMC-RP24-BLANK-AN-1U-MT The panel is designed for using with «AN» series modules (but is compatible with standard Keystone jacks) 6 6 The numbering of the ports on the back side panel makes it easier to guided during installation and further services **Accessories** Fast Cable Cable «AN» Series Termination Cutter: Stripper: FT modules with angled ports, Fast NMC-502C NMC-S501B Tool: terminating tool NMC-FT-TOOL or 110 / Krone knife NMC-FT-TOOL NMC-222 NMC-3640RB

The patch panels offer removable organizers for routing incoming cables.

The manufacturer reserves the right to alter the appearance and characteristics of the product, without compromising the product's functionality



### **Specifications**

	NMC-RP24-BLANK-AN-1U-MT					
Туре	Shielded					
Ports	24					
Type of module to be installed	Keystone (no wider than 17 mm)					
Marking	All ports are numbered, there are additional labeling area					
Installation	19" Cabinet or rack					
Height	1 U (44.5 mm)					
Depth	88 mm					
Housing Material	Nickel-plated steel, 1.5 mm					
Color	Metallic (Nickel)					
Temperature Ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating -10 to +60 ° C					
Packaging	Cardboard box					
Warranty	1 Year					

#### Selection Guide

Туре	Cat.	Modules series«Fast Termination» For quick sealing NMC-FT-TOOL or a 110 / KRONE knife			Modules «NT» series	Modules for punch down tool with	
		Basic (FT)	With shutters (ST)	Angled jacks (AN)	Tool-less	a 110/KRONE knife	
Shielded	6 <sub>A</sub>	-	-	NMC-KJSA2-AN-MT	-	-	
	6	-	-	NMC-KJSE2-AN-MT	-	-	
	5e	-	-	NMC-KJSD2-AN-MT	-	-	
Unshielded	6	-	-	NMC-KJUE2-AN-WT	-	-	
	5e	-	-	NMC-KJUD2-AN-WT	-	-	
	3	-	-	_	-	-	

### **Ordering Table**

Part Number	Ports	Height, U	Individual package		Freight package		
			Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMC-RP24-BLANK-AN-1U-MT	24	0.5	510x80x60	0.800	15 pcs.	515x400x230	13.1



# NMC-RP24-BLANK-AN-1U-MT

1U, 24 ports under UTP/STP module with angled keystone jacks (series AN)

## Package Content

Patch panel - 1pc. Cable organizer - 1 pc. Cable tie - 24 pcs. Grounding Wire - 1 pc. Screw-washer-nut - 4 pcs. Installation Instruction - 1 pc.

The manufacturer reserves the right to alter the appearance and characteristics of the product, without compromising the product's functionality